25 HP Reciprocating

96 CFM @ 175 PSI

Basic Compressor

Features

- Heavy Duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- Industrial grade electric motor
- ASME tested powder coated steel tank
- 4 grove B width motor pulley

- All UL electrical controls
- Access to compressor valves without compressor head removal
- Auto start stop
- Fully enclosed belt guard
- Centrifugal unloader
- Heavy duty air filter
- Swedish steel valves
- Torrington needle bearings



Air cooled after cooler Elite unit

Elite Compressor Features

- All basic features
- Belt guard after cooler
- Low oil monitor
- Magnetic starter mounted and wired
- Automatic tank drain
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
B253H129	3	208-230-460	120 Gallon Horizontal	Basic	70	38	60	63	32
B253H129-E	3	208-230-460	120 Gallon Horizontal	Elite	70	38	60	63	32
B253H249	3	208-230-460	240 Gallon Horizontal	Basic	85	46	72	63	32
B253H249-E	3	208-230-460	240 Gallon Horizontal	Elite	85	46	72	63	32

No Start Up Kit Required

Optional 2-year Pump Warranty Available. See catalog for additional options.



Compressed Air Systems

Simplicity. It's What We Do www.compressed-air-systems.com

